



| Magnetic properties                  | Conditions   | Min    | Typ | Max | Unit |
|--------------------------------------|--|--------|-----|-----|------|
| Pull-In excitation (Reference value) | Reed switch unmodified<br>measured in coil- "define operation" | 40     |     | 60  | AT   |
| Test-Coil                            | Reed switch unmodified   | KMS-01 |     |     |      |

| Contact data 55            | Conditions   | Min     | Typ | Max | Unit |
|----------------------------|--|---------|-----|-----|------|
| Contact-No.                |  | 55      |     |     |      |
| Contact-form               |  | A       |     |     |      |
| Contact-material           |  | Rhodium |     |     |      |
| Contact rating             | Any DC combination of V & A<br>not to exceed their individual max.'s |         |     | 50  | W    |
| Switching voltage          | DC or Peak AC  |         |     | 100 | V    |
| Switching current          | DC or Peak AC  |         |     | 0,5 | A    |
| Carry current              | DC or Peak AC  |         |     | 1   | A    |
| Contact resistance static  | Measured with 40% overdrive<br>Start Value                           |         |     | 150 | mOhm |
| Contact resistance dynamic | Maximum value 1,5 ms after excitation<br>Start Value                 |         |     | 200 | mOhm |
| Insulation resistance      | RH <45 %, 100 V test voltage   | 1       |     |     | GOhm |
| Breakdown voltage          | according to IEC 255-5   | 200     |     |     | VDC  |
| Operate time incl. bounce  | measured with 40% overdrive  |         |     | 1   | ms   |
| Release time               | measured with no coil excitation                                     |         |     | 0,1 | ms   |
| Capacity                   | @ 10 kHz across open switch  |         | 0,3 |     | pF   |

| Contact dimensions | Conditions                     | Min | Typ  | Max | Unit |
|--------------------|--------------------------------|-----|------|-----|------|
| Overall length     | Tolerance according to drawing |     | 44,1 |     | mm   |
| Glass body length  | Tolerance according to drawing |     | 16,5 |     | mm   |

| Environmental data    | Conditions                         | Min | Typ | Max | Unit |
|-----------------------|------------------------------------|-----|-----|-----|------|
| Shock                 | 1/2 sine, duration 11ms, in 3 axis |     |     | 50  | g    |
| Vibration             | from 10 - 2000 Hz                  |     |     | 20  | g    |
| Ambient temperature   |                                    | -20 |     | 130 | °C   |
| Storage temperature   |                                    | -55 |     | 130 | °C   |
| Soldering temperature | wave soldering max. 5 sec.         |     |     | 260 | °C   |